



SH-2500-UNI-B



SH-2500-UNI-E

Vacuum Lifting Device SH-2500-UNI

- ▶ **Main Body** – robust and compact for use on the building site.
- ▶ **Working load limit**
Type SH-2500-UNI up to 2,500 kg at -0.6 bar. The working load limit is dependent on the suction plate used. Higher carrying capacities available on request.
- ▶ **Safety Devices**
 1. Vacuum gauge
 2. Safety vacuum storage tank
 3. Pressure relieve valve
 4. **NEW**: Acoustic warning device with inbuilt intelligence. Batteries last approx. 1 year.
- ▶ **Various Means of Power**
 - E = electric, 230 Volt, single phase
 - B = by integral petrol engine
- ▶ Operating handle in ergonomic position.
- ▶ Motor-protecting switch, "Schuko" connector including connecting plug (only for SH-2500-UNI-E).
- ▶ Manually operated valve for vacuum "on/off".
- ▶ Fitted as standard with chain compartment and load securing chain.

Please note:

In no time the SH can be adapted using the MICROJUMBO MJ attachments for laying slabs by hand. Smaller components of stone and concrete slabs, 15 up to 150 kg – can then be safely transported and laid (see page 5.5).

Type	Power	Working Load Limit WLL kg (lbs)	Dead Weight (without suction plate) kg (lbs)	Order-Number
SH-2500-UNI-E**	electric, 230 Volt single phase	2,500* (5,500)*	96 (210)	5240.0044
SH-2500-UNI-B	petrol engine 2,9 kW	2,500* (5,500)*	100 (220)	5240.0043

Suction plates and additional beneficial attachments see type list page 5.19

* Value at 600 mbar low pressure. ** Plug type F, 230 V